

QUOTATION SHEET

Picture	Description	Item No.	Dimension(mm)	MOQ	PCL/CTN	Packing size (mm)			CBM	G W (kg)	N W (kg)
						L	W	H			
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 14.2L * 220V, 500W * Timing range: 24 hours, temperature adjustment from 20 to 90 degrees	PP-06A01	354x270x325	10	1	445	345	380	0.058	8	7
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 390*360mm, mesh hole: 8mm, Upper and lower grid spacing: 35mm * Capacity: 59L * 220V, 1000W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-01	545x420x180	10	1	600	480	450	0.130	17	15
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 390*360mm, mesh hole: 8mm, Upper and lower grid spacing: 35mm * Capacity: 59L * 220V, 1000W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-01(T)	545x420x180	10	1	600	480	450	0.130	17	15
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 45L * 220V, 800W * Timing range: 30 hours, temperature adjustment from 40 to 90 degrees	PP-06	420x315x450	10	1	495	370	505	0.092	13	12
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 45L * 220V, 500W * Timing range: 30 hours, temperature adjustment from 33 to 80 degrees	PP-03	410x295x290	10	1	500	370	340	0.063	8.5	7.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 45L * 220V, 500W * Timing range: 24 hours, temperature adjustment from 20 to 90 degrees	PP-03(T)	410x295x290	10	1	500	370	340	0.063	8.5	7.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 23L * 220V, 500W * Timing range: 30 hours, temperature adjustment from 33 to 80 degrees	PP-03(G)	410x295x290	10	1	500	370	340	0.063	8.5	7.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 23L * 220V, 500W * Timing range: 24 hours, temperature adjustment from 30 to 90 degrees	PP-03(TG)	410x295x290	10	1	500	370	340	0.063	8.5	7.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 15L * 220V, 500W * Timing range: 15 hours, temperature adjustment from 30 to 90 degrees	PP-04	275x370x320	10	1	330	375	320	0.040	7.3	6.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 250*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 15L * 220V, 500W * Timing range: 15 hours, temperature adjustment from 30 to 90 degrees	PP-04-H	275x370x320	10	1	330	375	320	0.040	7.3	6.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 42L * 220V, 500W * Timing range: 24 hours, temperature adjustment from 20 to 90 degrees	PP-06B	375x266x240	10	1	425	335	290	0.041	6.25	5.25
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 290*250mm, mesh hole: 2.7mm, Upper and lower grid spacing: 35mm * Capacity: 14L * 220V, 500W * Timing range: 24 hours, temperature adjustment from 20 to 90 degrees	PP-06B-H	288x366x113	10	1	445	350	380	0.059	8.3	7.3
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 390*360mm, mesh hole: 8mm, Upper and lower grid spacing: 35mm * Capacity: 100L * 220V, 1500W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-02	420x454x630	10	1	635	485	705	0.217	25	22.8
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 370*370mm, mesh hole: 5mm, Upper and lower grid spacing: 37mm * Capacity: 110L * 220V, 1800W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-02(T)	420x550x740	10	1	610	485	805	0.238	25	22
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 370*370mm, mesh hole: 8mm, Upper and lower grid spacing: 38mm * Capacity: 297L * 220V, 3000W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-22	550x720x1080	10	1	660	830	1270	0.696	65	59
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 390*360mm, mesh hole: 8mm, Upper and lower grid spacing: 35mm * Capacity: 220L * 220V, 3150W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-32	420x595x1420	10	1	720	500	1510	0.544	53	47.5
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 670*670mm, mesh hole: 12mm, Upper and lower grid spacing: 50mm * Capacity: 600L * 220V, 5850W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-00	700x880x1380	10	1	1010	800	1570	1.269	140	95
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 390*360mm, mesh hole: 8mm, Upper and lower grid spacing: 35mm * Capacity: 425L * 220V, 7400W * Timing range: 15 hours, temperature adjustment from 40 to 90 degrees	PP-88A	870x565x1550	10	1	960	680	1730	1.129	136	104.5
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 259*205mm, mesh hole: 2.7mm, Upper and lower grid spacing: 28mm * Capacity: 6.8L * 220V, 400W * Timing range: 24 hours, temperature adjustment from 20 to 90 degrees	PP-04A01	293x290x200	10	1	340	335	245	0.028	3	
	* Rack: S5304 * Outer case: S5201, 0.8mm thickness * Aluminum alloy handle * Grid size: 259*205mm, mesh hole: 2.7mm, Upper and lower grid spacing: 28mm * Capacity: 6.7L * 220V, 400W * Timing range: 24 hours, temperature adjustment from 20 to 90 degrees	PP-05A	282x347x206	10	1	380	355	255	0.034	5.7	4.7